

# KALIX



## 2 VERSIONEN

- CC: P1PVCDKY / P1PVKY
- HC: P1PVCDHSY / P1PVHSY, P1PVCDHSKY/P1PVHSKY Tri- Temp

## BESCHREIBUNG

- Soft-Touch-Tasten mit Kontrollleuchte
- einfacher Zugriff auf Filter durch abnehmbare Fronttür
- Platz zur Befüllung von Sportflaschen, Karaffen usw.
- einfache Wartung und Reinigung durch zweiteiligen Kühlbehälter
- erhältlich in Cook 'n Cold, Hot 'n Cold, Tri-Temp
- integrierter Becherspender
- herausnehmbare, selbstentleernde Tropfschale



**Model**

Weight

Dimensions (H x W x D)

Performance (litres of cold water / hour)

! At 21°C bottle, 21°C ambient

! At 32°C bottle, 32°C ambient

Refrigerant type

Refrigerant charge

Cold tank capacity

Power consumption

**P1PVKY**

23,4 kg

112 cm x 32 cm x 38 cm

20,0 litres per hour

8.5 litres per hour

R134a

60 g

1.5 litres

100 Watt

**Model**

Weight

Dimensions (H x W x D)

Performance (litres of cold water / hour)

! At 21°C bottle, 21°C ambient

! At 32°C bottle, 32°C ambient

Refrigerant type

Refrigerant charge

Cold tank capacity

Power consumption

**P1PVCDKY**

23,5 kg

112 cm x 32 cm x 38 cm

20,0 litres per hour

8.5 litres per hour

R134a

60 g

1.5 litres

100 Watt



**Model**

Weight

Dimensions (H x W x D)

Performance (litres of cold water / hour)

! At 21°C bottle, 21°C ambient

! At 32°C bottle, 32°C ambient

Performance (litres of hot water / hour)

Refrigerant type

Refrigerant charge

Cold tank capacity

Hot tank capacity

Power consumption

**P1PVHSY**

24,6 kg

112 cm x 32 cm x 38 cm

20,0 litres per hour

8.5 litres per hour

7.9

R134a

**60 g**

1.5 litres

1.5 litres

**620 Watt****Model**

Weight

Dimensions (H x W x D)

Performance (litres of cold water / hour)

! At 21°C bottle, 21°C ambient

! At 32°C bottle, 32°C ambient

Performance (litres of hot water / hour)

Refrigerant type

Refrigerant charge

Cold tank capacity

Hot tank capacity

Power consumption

**P1PVCDHSY**

24,7 kg

112 cm x 32 cm x 38 cm

20,0 litres per hour

8.5 litres per hour

7.9

R134a

**60 g**

1.5 litres

1.5 litres

**620 Watt**

**Model**

Weight

Dimensions (H x W x D)

Performance (litres of cold water / hour)

! At 21°C bottle, 21°C ambient

! At 32°C bottle, 32°C ambient

Performance (litres of hot water / hour)

Refrigerant type

Refrigerant charge

Cold tank capacity

Hot tank capacity

Power consumption

**P1PVHSKY**

24,6 kg

112 cm x 32 cm x 38 cm

20,0 litres per hour

8.5 litres per hour

7.9

R134a

60 g

1.5 litres

1.5 litres

620 Watt

**Model**

Weight

Dimensions (H x W x D)

Performance (litres of cold water / hour)

! At 21°C bottle, 21°C ambient

! At 32°C bottle, 32°C ambient

Performance (litres of hot water / hour)

Refrigerant type

Refrigerant charge

Cold tank capacity

Hot tank capacity

Power consumption

**P1PVCDHSKY**

24,7 kg

112 cm x 32 cm x 38 cm

20,0 litres per hour

8.5 litres per hour

7.9

R134a

60 g

1.5 litres

1.5 litres

620 Watt